

Power-PRO TL Specifications

Model Number	6550
Height ¹ (infinite height positioning between lowest and highest position)	
Lowest Position	19.5" (49.5 cm)
Highest Position	38" (96.5 cm)
Length	
Standard	76.5" (194.3 cm)
Minimum	55" (139.7 cm)
Width	23" (58 cm)
Weight ²	145 lbs (66 kg)
Wheels	
Diameter	6" (15 cm)
Width	2" (5 cm)
Articulation	
Backrest	0 – 75°
Shock Position	+15°
Knee Gatch	30°
Maximum Weight Capacity	700 lbs (318 kg)
Minimum Operator Required	
Occupied Cot	2
Unoccupied Cot	1
Recommended Cot Fastener System	
Floor Mount ³	Model 6385, 6386, 6387

¹ Height measured from bottom of mattress, at seat section, to ground level.

² Cot is weighed with one battery, without mattress and restraints.

³ Designed to be compatible with competitive ambulance cots. Floor plate and floor track mounting configurations available.

The Power-PRO TL is designed to be compatible with competitive cot fastener systems.

Stryker reserves the right to change specifications without notice.

In-service video included with each order.

International patents pending.

Optional Features

- Heavy duty two- and three-stage IV poles (patient right or left)
- Restraint extender (36"/91.4 cm)
- Rigid push bars (removable)
- Base storage net
- Pocketed backrest storage pouch
- Equipment hook
- Four-corner wheel locks
- DEWALT® battery charger (12V, 110V and 220V models available)

The information presented in this brochure is intended to demonstrate a Stryker product. Always refer to the package insert, product label and/or user instructions before using any Stryker product. Products may not be available in all markets. Product availability is subject to the regulatory or medical practices that govern individual markets. Please contact your Stryker Account Manager if you have questions about the availability of Stryker products in your area.

Products referenced with ™ designation are trademarks of Stryker.

Products referenced with ® designation are registered trademarks of Stryker.

Mkt Lit-145-01 May 2007 Rev B
PC/SCG-2.5M-0507, 07-SEM-1764

Copyright © 2007 Stryker
Printed in USA

stryker®

Joint Replacements

Trauma, Extremities & Deformities

Craniomaxillofacial

Spine

Biologics

Surgical Products

Neuro & ENT

Interventional Pain

Navigation

Endoscopy

Communications

Imaging

Patient Handling Equipment

EMS Equipment

Rehabilitation Services

3800 E. Centre Ave.
Portage, MI 49002 USA

t: 269 329 2100
f: 269 329 2315
toll free: 800 784 4336

Stryker UK Limited
Stryker House
Hambridge Road
Newbury, Berkshire
RG14 5EG, UK

t: +44 (0) 1635 262444
f: +44 (0) 1635 36400
PHE@stryker.com

www.ems.stryker.com
www.stryker.co.uk

stryker®

EMS Equipment

Power-PRO™ TL
powered
ambulance cot

RUGGED

Because lives depend on it.™

Power-PRO TL

powered
ambulance cot

power to reduce the risk of injury

Power-PRO TL

Extensive input and feedback from pre-hospital care professionals have qualified the need for an ambulance cot that reduces the amount of manual lifting caregivers experience on a day-to-day basis.

- Innovative battery-powered hydraulic system raises and lowers the patient with the touch of a button
- Easy-to-use manual back-up system provides complete cot operation in the event of power loss
- Foot end mounted DeWALT® Battery System is accessible and easily changed in any situation
- Retractable head and foot section allows cot to be shortened in any height position for maximum versatility

700^{lb}
capacity

Electrical and Mechanical Safety Certifications:



IPX6 IEC-60601
BS EN-1789



Rigid Push Bars

A Stryker exclusive; unprecedented manoeuvrability in any situation. (optional)



Retractable Head and Foot Sections

A Stryker exclusive; maximizes manoeuvrability in tight spaces.



Cot Fastener System

Welded stainless steel construction for unprecedented durability. Available in floor plate and floor track mounting configurations.

Pneumatic Backrest

A Stryker innovation. Provides superior operator control.

Fold Down Side Rails

A Stryker innovation. Fully operational in confined spaces.

Shock, Knee Gatch or Flat Leg Positioning

For patient comfort and maximum versatility.

Larger Patient Surface

Easily accommodates taller patients. Maximizes space between patient and operator.

Patented X-Frame

Proven reliability.

Hydraulic Lift System

Battery-powered hydraulic lift system with manual back-up for operator confidence.

Battery and Battery-Release Control

Accessible and easily changed in any situation.



Steer-lock System

Wheel can swivel or lock into straight-line position, maximizing manoeuvrability on inclined surfaces.

Oversized Wheels

Less force required to roll.

Select Features



Power Controls

Contoured control buttons assist the operator with touch recognition for ease of operation.

Manual Back-up Release Handle

Allows complete cot operation in the event of power loss.



Industrial Grade 24V DeWALT® Battery System

Powers the cot through 20 complete calls.*



Marine Grade Hydraulic System

Provides reliable operation in harsh conditions.

* Battery life may vary depending on patient weight and environmental conditions.



DeWALT is a registered trademark of Black & Decker Inc.