Fluoroscopy

stryker

Stretcher

Access & functionality

Our Fluoroscopy Stretcher's features are designed to simplify operation and minimise the need to reposition the patient during fluoroscopic imaging.

Optional accessory rail accommodates surgical attachments.

Four-wheel brake system helps secure treatment platform.



Enhanced imaging capabilities

U-shaped base and full-length
C-arm access enhance
imaging capabilities. High
height litter option adds 18
cm to low and high height to
accommodate different size
C-arms.



Patient access

Siderails fold down and out of the way for improved patient access.



Pneumatic backrest

Fibres in pneumatic backrest at both ends improves imaging access and helps reduce the need to reposition the patient.



Stryker Australia Pty Ltd

8 Herbert Street St Leonards NSW 2065 61 2 9467 1000 www.stryker.com.au

Stryker New Zealand Limited

PO Box 17-136 Greenlane, Auckland 1546, New Zealand 64 9 573 1890 www.stryker.com



Fluoroscopy Stretcher

Standard features

- 5.1 cm (2") mattress
- 15.2 cm (6") nonconductive casters
- Dual end-mounted foot control hydraulics
- Dual fiberesin pneumatic backrest
- Fold-down siderails
- Four corner roller bumpers
- Four IV receptacles
- Four-wheel, steel-ring brake system with dual end activators
- Radiolucent litter top
- · Locking-caster steering with dual end activators
- · U-shaped base
- 2-stage permanent IV pole
- Integrated accessory rail

Optional features

- Footboard/chartholder
- IV poles (permanent folding two- or three-stage or removable)
- · Restraint straps
- Upright oxygen bottle holder
- High height option adds 18 cm to low and high height

Specifications

| Model number | 1080 |
|--------------------------------|---------------------------|
| Overall length | 221.0 cm (87") |
| Overall width (siderails down) | 77.5 cm (30.5") |
| Weight capacity | 226.8 kg (500 lb.) |
| Height range | |
| High | 83.2 cm (32.75") |
| Low | 59.7 cm (23.5") |
| Litter positioning | |
| Dual backrest operation | 0° - 90° |
| Trend./reverse Trend. | ±8° |
| Patient surface | 66 x 213 cm (26" x 84") |
| Fluoroscopy window | 70 x 168 cm (27.5" x 66") |
| Siderails | 33 x 140 cm (13" x 55") |
| Caster diameter | 15.2 cm (6") |
| C-arm access width | 137.2 cm (54") |

A healthcare professional must always rely on his or her own professional clinical judgment when deciding whether to use a particular product when treating a particular patient. Stryker does not dispense medical advice and recommends that healthcare professionals be trained in the use of any particular product before using it. The information presented is intended to demonstrate the breadth of Stryker product offerings. A healthcare professional must always refer to the package insert, product label and/or instructions for use before using any Stryker product. Products may not be available in all markets because product availability is subject to the regulatory and/or medical practices in individual markets. Please contact your Stryker representative if you have questions about the availability of Stryker products in your area. Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: Stryker. All other trademarks are trademarks of their respective owners or holders.

For more information please contact your local Stryker sales representative.