



Ultra Comfort SE™

Stretcher Support Surface



The next generation of stretcher support surfaces

When we developed the SE series of stretcher surfaces, we focused our innovative design on aiding in proactive prevention.

The Ultra Comfort SE Support Surface was designed with the overall patient experience in mind and has specific features to assist in improving outcomes.¹

Key Features

- Thermoplastic polyurethane (TPU) cover* engineered for ease of use and provides increased chemical resistance
- RF welded seams limit fluid ingress and infiltration
- Three-sided zipper allows for inspection of the condition of internal components
- 700 lb. weight capacity
- X-ray compatible



Compatible with our stretchers

The Ultra Comfort SE Support Surfaces' design and thickness allows for compatibility with Stryker's stretchers



Welded seams

Seams are a common problem area for infection. Our covers are sealed with a specific type of electromagnetic bonding utilizing RF welding to limit fluid ingress and infiltration.



Three-sided zipper

Caregivers can now fully inspect the condition of internal components of their stretcher surface with the new three-sided zipper.



Durability

The Ultra Comfort SE Support Surface's cover is engineered for ease of use, especially during the maintenance and care process. It is made with a Thermoplastic Polyurethane (TPU) cover* for increased chemical resistance.

Ultra Comfort SE

Stretcher Support Surface



Standard features

- Thermoplastic polyurethane (TPU) cover*
- Welded seams
- Three-sided zipper
- 700 lb. weight capacity
- Compatible with Stryker's stretchers

Optional features

- Polycarbonate polyurethane (PCPU) cover

Specifications

Model number	1703-034-300	1704-034-300	1704-034-600
Overall width	30 in (76 cm)	30 in (76 cm)	26 in (66 cm)
Overall length	76 in (193 cm)	76 in (193cm)	76 in (193 cm)
Thickness	3 in (7.6 cm)	4 in (10 cm)	4 in (10 cm)
Weight capacity	700 lb. (317 kg)	700 lb. (317 kg)	700 lb. (317 kg)

Flammability standards: USA 16 CFR 1632; CALTB117

Flammability standards for optional polycarbonate polyurethane cover: CALTB117; 16CFR1632; CGSB CAN 2-4.2 Method 27.7-M77; BS EN 597-1; BS EN 597-2; CAL TB129; 16CFR1633; BS 6807, Clause 9; BFD IX-11; UNI9175

Stryker reserves the right to change specifications without notice.

Warranty

Stryker Medical, a division of Stryker Corporation ("Stryker"), warrants that its Model 1703 and 1704 Ultra Comfort SE Support Surface. Product will be free from defects in material and workmanship. Stryker's warranty covers only the following items during normal use as follows:

- Core assembly: one (1) year
- Fire barrier: one (1) year
- Support surface cover: one (1) year

*Optional Polycarbonate Polyurethane cover (PCPU) cover available

1. Recommended to be implemented in combination with clinical evaluation of risk factors and skin assessments made by a healthcare professional.

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: **Ultra Comfort SE, Stryker**. All other trademarks are trademarks of their respective owners or holder.

3800 E. Centre Avenue
Portage, MI 49002 USA
t: 269 329 2100
toll free: 800 327 0770

patienthandling.stryker.com

Mkt Lit-1439 15 DEC 2016 Rev B.2
Copyright © 2017 Stryker
Printed in U.S.A.